

## 4 DIGIT TIMER

Model : DT 70A



### Features

- 4 Digit Seven Segment LED Display
- Seconds, Minutes, Hours Configurable
- Selectable Resolution 0.01 / 0.1 / 1
- 2 Relay Outputs with Selectable Delay Mode
- Front End Reset with Protection
- External Start / hold / Reset Options
- 10 Years Memory Backup
- Universal Supply Voltage 90 to 270V AC / DC

## Application

- Automotive Industries
- Beverage Industries
- Pipe Industries
- Thermal Industries
- Long term Testing Lab
- All Kind of Time based Applications

## Technical Specifications

<b>Model</b>	<b>DT 70 A</b>
<b>External Input</b>	<b>START / HOLD / RESET ( potential free contact inputs)</b>
<b>Range</b>	<b>99.59, 999.9, 9999 Secs / Mins / Hrs(Programmable)</b>
<b>Resolution</b>	<b>0.01 Sec/Min/Hr</b>
<b>Accuracy</b>	<b>± 0.05 Of Selected Range or 50msec (whichever Is First)</b>
<b>Display</b>	<b>4 Digit 0.5" RED Seven Segment LED</b>
<b>Relay Output</b>	<b>2 NO , 2 NC 5 A Rated Relay</b>
<b>Working temperature</b>	<b>0 - 50 °C</b>
<b>Power Supply</b>	<b>90 to 270V AC / DC 50Hz</b>
<b>Dimension</b>	<b>72 x 72 x 110 mm</b>
<b>Weight</b>	<b>200 grams (Approx.)</b>

Note: Due to continuous product improvements, Published specifications may change with out notice

## SANSEL INSTRUMENTS AND CONTROLS SANSEL CALIBRATION LABORATORIES

**NABL** Accredited Calibration Lab ( Thermal, Mechanical, Electro-Technical Parameters )

1 / 46 , Ganga Nagar, MMDA Colony , Maduravoyal , Chennai - 600 095. INDIA

☎ +91 44 2378 3951 , +91 44 6534 0391 📞 +91 98401 49941 ✉ enquiry@ sansel.net